



WAM[®] Inc.



SILO VENTING FILTER

SILOTOP[®]

R01 Series



**EXCELLENT FOR
READY MIXED
INDUSTRIES !**

- ✓ More comfortable maintenance height
- ✓ Lockable hinged cover
- ✓ Free access to filter elements and in cover integrated cleaning system
- ✓ Easier replacement of filter elements
- ✓ Flanged silo connection

SILOTOP®

Obstruction-free extruded aluminum manifolds for optimum air flow

Weather protection cover with lockable snap hook



Drain point

BODY	FILTER SURFACE	MAX. HEIGHT WHEN CLOSED	MAX. HEIGHT WHEN OPEN	lbs (kg)
Ø 31.5 inches (800 mm)	264 ft² (24.5m²)	45 inches (1145 mm)	73 inches (1850 mm)	225 (102)

Aluminum air tank (corrosion-resistant)

Manifolds integrated into the hood



Weather protection cover "Autolock" hinges self-locking when open



Filter element clamps reduce maintenance time



Heavy-duty 16 gauge 304 stainless steel body with bottom flange - thickness 0.04

Steel frame with integrated birdcage



Inspection hatch



CARTRIDGES INCLUDED!

POLYPLEAT® filter cartridges with integrated Venturi shafts guarantee optimum filter surface - air to cloth ratio





Huge inventory available for immediate delivery!



OTHER PRODUCTS



Cement Screw Conveyors



Vertical Srew Conveyors



Butterfly Valves



Slide Valves



Pressure Relief Valves



Level Indicators



Rotary Valves



Pinch Valves

N.B.: Rights reserved to modify technical specifications.

WAM.035.05.US 08/02



INDUSTRIAL EQUIPMENT INCORPORATED
Concrete, Aggregate, and Material Handling Equipment
Concrete Solutions with Rock Solid Results
800-792-7427

